

WAVESEAL CLAMP



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 12:38 PM

SKU

: 21947

BRAND

: DIXON VALVE

MODEL

: WSS22

Applications:

Provides optimal retention in applications involving thermal cycling and / or high vibration.

Features:

Produces a sealing O-ring effect that prevents leakage

Construction:

5/16" head screw

Band: 201/301 Stainless Steel

Liner & Housing: 304 Stainless Steel

Screw: 410 Stainless Steel

Installation

Suggested installation torque 50-70 inch pounds, maximum recommended torque 70 inch pounds

Note:

Clamps sold 10 per box

Safety notes:

Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any assembly installed with this clamp.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|------------------------------|---------------------|
| Factory Part Number | WSS22 |
| Hose OD From | 1-7/16" |
| Hose OD To | 1-11/16" |
| Material | Stainless Steel |
| Width | 9/16" |
| Mandatory Pkg/Box Qty | 10 |
| Weight Lb | 0.0700 |
| Torque | 70 in. lbs. Maximum |