

ASME AIR TANK RECEIVER MANIFOLD ASSEMBLY WITH AIR KING COUPLERS



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 06/10/2026 03:50 PM

SKU

: 482

MARCA

: DIXON VALVE

MODELO

: 1217AR-4AK

Applications:

Safely distributes compressed air to machines and tools.

Service:

- 7 gallon capacity provides air reserve needed for operation of tools
- 200 PSI maximum working pressure for tank (Working pressure of the system is limited to maximum working pressure of the components, i.e. 150 PSI for Air King)

Features:

- All tank outlets have female NPT threads
- Portable - easy carry handles standard
- Solid base with mounting holes standard
- Approximate tank dimensions are 12" x 17"; 40" x 24" with frame
- Painted safety orange

Components:

- Spring-loaded safety shut-off valves (cut-off flow rate 160-180 CFM at 90 PSI)
- Safety pop-off valve (200 PSI) to protect against over-pressurizing of tank
- 0-300 PSI gauge
- Locking handle ball valves
- Drain valve provides for removal of accumulated oil and water

Codes and Standards:

- Built to ASME Code, National Board registered
- Conforms to OSHA Standards 1910.169 and 1926.306

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Brand	DIXON Valve
Factory Part Number	1217AR-4AK
Material	Steel
Capacity	7 gallons
Working Pressure	200 PSI
Weight Lb	92.0000