

## DIXON® CAM & GROOVE ADAPTER X 150# ANSI FLANGE



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/21/2026 02:37 PM

SKU

: 2101

MARCA

: DIXON VALVE

MODELO

: 200-AL-SSANSI

Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Use:

Flanges are designed to mate with #150 ANSI flange

Specifications:

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:

Flange has raised face

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Factory Part Number</b>        | 200-AL-SSANSI       |
| <b>Material</b>                   | 316 Stainless Steel |
| <b>Maximum Operating Pressure</b> | 250 PSI             |
| <b>Size</b>                       | 2"                  |
| <b>Thickness</b>                  | 3/4"                |
| <b>Weight Lb</b>                  | 5.7000              |