A-SERIES PNEUMATIC FEMALE THREADED COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/25/2026 07:35 AM

SKU
: 3000

MARCA
: DIXON VALVE

MODELO
: 2AF1-B

Applications:
A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 500 PSI (35 bar) Maximum Working and 6,500 PSI (450 bar) Burst
Rated pressure for connected Brass Coupler & Steel Plug: 1,000 PSI (70 bar) Maximum Working and 8,000 PSI (550 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Couplers are constructed of brass with steel valve as standard
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Proprietary Astronautics

Safety notes:
Pressure rating given at ambient temperature 70°F (21°C).
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	2AF1-B
Hex	1/2"
Length	2.41"
Material	Brass
Maximum OD	0.77"
Pressure Rating	See Product Details
Thread	NPTF
Thread Size	1/8"
Weight Lb	0.1700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us