

## STEEL 3500 NIPPLE WITH FERRULE



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 06/22/2026 07:37 AM

SKU

: 22401

MARCA

: DIXON VALVE

MODELO

: 3518WF2

Use:

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.

To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

Features:

Low profile

Streamline appearance

Construction:

Zinc plated steel 3500 nipple

Carbon steel ferrule

Installation

Can be crimped or swaged-on to achieve maximum coupling sealing and retention

Note:

For crimp or swage recommendations, contact Dixon.

Safety notes:

For air and water service only

To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.

## ESPECIFICACIONES TÉCNICAS

<b>Factory Part Number</b>	3518WF2
<b>Hose OD From</b>	1-34/64"
<b>Hose OD To</b>	1-38/64"
<b>Hose Size</b>	1"
<b>Male Thread</b>	NPT
<b>Male Thread Size</b>	1"
<b>Material</b>	Steel
<b>Pressure Rating</b>	600 PSI at 70°F (21°C)
<b>Weight Lb</b>	1.0000