

## 15K THREADED COUPLER



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/26/2026 01:19 PM

SKU

: 4995

MARCA

: DIXON VALVE

MODELO

: 4TDF4-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock  
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### ESPECIFICACIONES TÉCNICAS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4TDF4-SS
<b>Length</b>	2.57"
<b>Material</b>	316L Stainless Steel
<b>Maximum OD</b>	1.85"
<b>Maximum Operating Pressure</b>	15,000 PSI
<b>Temperature Range</b>	-40°F - 250°F (-40°C - 121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/2"-14

**ESPECIFICACIONES TÉCNICAS**

**Weight Lb**

1.0500