

15K THREADED COUPLER



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 07/11/2026 03:25 PM

SKU

: 4995

MARCA

: DIXON VALVE

MODELO

: 4TDF4-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Factory Part Number	4TDF4-SS
Length	2.57"
Material	316L Stainless Steel
Maximum OD	1.85"
Maximum Operating Pressure	15,000 PSI
Temperature Range	-40°F - 250°F (-40°C - 121°C)
Thread	Female NPTF
Thread Size	1/2"-14

ESPECIFICACIONES TÉCNICAS

Weight Lb

1.0500