

AIR BRAKE MALE ELBOW

FECHA

: 08/02/2026 09:51 PM

SKU

: 6163

MARCA

: DIXON VALVE

MODELO

: 69NAB88VS

Applications:

Designed for use in air brake systems or cab controls

Use:

Utilize ribbed sleeve for compression and positive grip

Compatible tubing: SAE J844 type A and B

Specifications:

Meets D.O.T FMVSS 571.106 and SAE J246

Ref. SAE 100202 BA

Features:

Positive grip

Construction:

Machined from CA260, CA345 or CA377 brass

Pre-applied thread sealant

Thread sealant may be white or burnt orange

Installation

Cut tubing squarely- maximum of 15° angle allowable.

Check that port or mating part is clean and free of debris.

Insert tubing into fittings until it bottoms on seat.

Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

ESPECIFICACIONES TÉCNICAS

Factory Part Number	69NAB88VS
Flow	.33"
Material	Brass
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Thread	Straight x Pipe
Thread Size	11/16"-20 x 1/2"
Tube Size	1/2"
Weight Lb	0.2500
Working Pressure	150 PSI