

AIR BRAKE FEMALE ELBOW



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 09/07/2026 07:36 AM

SKU

: 6282

MARCA

: DIXON VALVE

MODELO

: 70NAB32

Applications:

Designed for use in air brake systems or cab controls

Use:

Utilize ribbed sleeve for compression and positive grip

Compatible tubing: SAE J844 type A and B

Specifications:

Meets D.O.T FMVSS 571.106 and SAE J246

Ref. SAE 100203 BA

Features:

Positive grip

Construction:

Machined from CA260, CA345 or CA377 brass

Installation

Cut tubing squarely- maximum of 15° angle allowable.

Check that port or mating part is clean and free of debris.

Insert tubing into fittings until it bottoms on seat.

Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	70NAB32
Flow	.087"
Material	Brass
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Thread	Straight x Pipe
Thread Size	5/16"-24 x 1/8"
Tube Size	3/16"
Weight Lb	0.0550
Working Pressure	150 PSI