

## ADS OUTALARM WITH CONDUCTIVITY PROBE FOR CONDUCTIVE FLUIDS



FECHA

: 06/13/2026 04:40 PM

SKU

: 6706

MARCA

: DIXON VALVE

MODELO

: A100CSS36A

### Applications:

Specifically designed for liquid terminal operation on batch loading and overfill protection, unloading, tank cars, tank trucks, marine barges, suitable for open and close dome

### Specifications:

Intrinsically safe design per ANSI / UL913 for Class I, Div1

### Features:

Totally self-contained- no wires, no tubing, external power

Rugged weather and corrosion resistant construction

No moving parts, conductivity sensor with integral splash shield

Groups A, B, C, & D Hazardous Areas

Requires no calibration or adjustment

Operates up to 5000 hours on single 9V alkaline battery

Adjustable insertion length through standard 1/2" NPT fitting

High intensity audible and flashing visual outputs

Graduated rod, laser engraved

Fail safe continuous battery monitor goes to alarm state on low battery

1/2" NPT gland standard

### Construction:

Stainless Steel and PTFE

### Available Options:

Optional opto-isolated solid state contact output

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

## ESPECIFICACIONES TÉCNICAS

<b>Description</b>	A100 Outalarm with conductivity probe
<b>Factory Part Number</b>	A100CSS36A
<b>Length</b>	36"
<b>Temperature Range</b>	-40°F to 325°F (-40°C to 162°C)