


A-SERIES PNEUMATIC FEMALE THREADED PLUG



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA
: 06/15/2026 02:17 PM

SKU
: 6722

MARCA
: DIXON VALVE

MODELO
: A1F1-B

Applications:

A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 500 PSI (35 bar)
Maximum Working and 15,500 PSI (1,070 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:

Proprietary Astronautics

Safety notes:

Pressure rating given at ambient temperature 70°F (21°C).

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/8"
Factory Part Number	A1F1-B
Flow	7 CFM at 100 PSI
Hex	1/2"
Length	1.26"
Material	Brass
Maximum OD	0.58"
Pressure Rating	See Product Details

ESPECIFICACIONES TÉCNICAS

Thread	NPTF
Thread Size	1/8"
Weight Lb	0.0300