

## AIR RELIEF VALVE FIXED PRESSURE FEMALE NPT



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 07/29/2026 06:16 PM

SKU

: 25864

MARCA

: DIXON VALVE

MODELO

: A2180/14

### Applications:

Designed specifically for use on trailer tanks containing dry bulk products. If a system blockage were to occur the valves are designed to vent to atmosphere once the valve pressure setting is achieved.

### Use:

Trailer/Tank Mounted Air Relief Valve

### Specifications:

Relieving capacity: 500 to 950 SCFM

### Features:

Installed cup seal deters tampering

Bayloy body eliminates thread galling

### Construction:

Bayloy vent cowl with aluminum upper

Bronze poppet

White Food Grade Silicone Diaphragm

### Available Options:

PVC coated wire lanyard available for securing air relief valves

### Note:

Relieving capacity (SCFM) varies dependent upon model and pressure setting. For specific rates please contact Dixon.

### Safety notes:

Not intended for blower service (for blower service applications see the 2182 series air relief valves)

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

|                        |                                        |
|------------------------|----------------------------------------|
| Component Material     | White Food Grade Silicone<br>Diaphragm |
| Factory Part Number    | A2180/14                               |
| Female Thread          | NPT                                    |
| Female Thread Size     | 2"                                     |
| Material               | Aluminum                               |
| Pressure Setting       | 14 PSI                                 |
| Set Pressure Tolerance | +1/0 PSI                               |
| Weight Lb              | 0.0100                                 |