

BOSS-LOCK CAM & GROOVE COUPLER X FEMALE NPSM



** Imágenes referenciales*

*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA

: 06/17/2026 04:16 PM

SKU

: 23063

MARCA

: DIXON VALVE

MODELO

: ADS400

Applications

Designed for the delivery of dry goods

Specifications

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Features

All Boss-Lock™ couplers are supplied with pull-safety clips.

Construction

Buna-N gasket

Available Options

Other gasket types are available, contact Dixon.

How it works

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

The cast-in lugs allow safety clips to be attached once the lugs are passed through slots in the special cam lever arms providing a positive locking action.

The pull ring safety clip simplifies the locking action on Boss-Lock couplers. No more inserting clips or dangling lanyards, just a twist and it's locked, giving you a low profile positive locking action.

Safety notes

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon

fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Material	356T6 Aluminum
Maximum Operating Pressure	100 PSI
Factory Part Number	ADS400
Seal	Buna-N
Size	4"
Weight Lb	2.0400