SAND BLAST QUICK COUPLING

FECHA
: 11/25/2026 07:45 AM

SKU
: 7118

MARCA
: DIXON VALVE

MODELO
: ASB75



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Sand blast couplings are designed for use on sand blast hose.

Features:
Supplied with screws

Installation
Ends of hose must be cut square to fit snug against metal end.
Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.
After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.
On quick couplings, insert safety clips.

Safety notes:
Abrasive blasting equipment must have hose safety cables or hose coupling safety clips installed
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	ASB75
Hose OD	1-1/2"
Hose Size	3/4"
Material	Aluminum
Pressure Rating	110 PSI at ambient temperature 70°F (21°C)
Weight Lb	0.4000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us