

## AIR RELIEF VALVE WITH TAPPED BLIND END



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/31/2026 12:40 PM

SKU

: 8706

MARCA

: DIXON VALVE

MODELO

: BARV-G150

### Applications:

Bleeding of a tube line where an air pocket has formed. This application calls for installation at the top of the tube.

Bleeding of a tube on the suction side of a pump. The suction side is bled automatically, before the pump starts, establishing a vacuum. Binding of air to liquid will be prevented, and so will subsequent cavitation. In this application the valve is mounted in front of the pump, on the top of the inlet tube.

### Features:

No special tools required

Ball and gaskets are replaceable

Valve seals are for both pressure and vacuum

### Construction:

The valve ball is constructed of FDA, 3A approved polypropylene.

1/8" NPT tap

All product contact surfaces have a radius of 1/4" or better.

### Available Options:

PTFE valve ball is available

Other gasket materials are available

### How it works:

Allows air to be removed from a line or container without the liquid flowing out. Its design does not allow air to enter the line or container, even if subjected to a negative pressure. It is a double-seated valve with a freely moving polypropylene ball. The ball, which is lighter than water, closes against the upper or lower seat, depending on the pressure conditions.

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

<b>Factory Part Number</b>	BARV-G150
<b>Material</b>	304 Stainless Steel
<b>Maximum Operating Pressure</b>	145 PSI
<b>Maximum Temperature</b>	212°F (100°C)
<b>Size</b>	1-1/2"
<b>Weight Lb</b>	1.7500