BACKFLOW PREVENTER

FECHA
: 11/25/2026 10:10 AM

SKU
: 8908

MARCA
: DIXON VALVE

MODELO
: BFP200



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Designed to give maximum protection against backflow caused by back-pressure or back-siphonage from a cross-connection wherein a contaminant hazard exists (i.e. a health hazard), or a pollutant hazard exists (i.e. a non-hazard).

Specifications:
Underwriters listed
Factory Mutual approved
Meets Foundation for Cross Connection Control and Hydraulic Research at University of Southern California Manual Section 10, ASSE 1015, AWWA C-510 and CSA B64.4 specifications

Features:
Consists of two spring-loaded poppet type valves and a mechanically independent, hydraulically dependent pressure differential relief valve
Three top mounted test cocks ensure easy access during repair and maintenance when unit is installed in tight places

Note:
Create a Fire Hydrant Backflow Preventer using the RSMSA25F20T and the DMH2025F

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Material	Brass
Factory Part Number	BFP200
Temperature Range	33°F to 180°F (.6°C to 82°C)
Thread	NPT
Thread Size	2"
Weight Lb	40.1000
Working Pressure	175 PSIG

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us