

BACKFLOW PREVENTER

FECHA
: 06/13/2026 11:10 AM

SKU
: 8908

MARCA
: DIXON VALVE

MODELO
: BFP200



Applications:

Designed to give maximum protection against backflow caused by back-pressure or back-siphonage from a cross-connection wherein a contaminant hazard exists (i.e. a health hazard), or a pollutant hazard exists (i.e. a non-hazard).

Specifications:

Underwriters listed

Factory Mutual approved

Meets Foundation for Cross Connection Control and Hydraulic Research at University of Southern California Manual Section 10, ASSE 1015, AWWA C-510 and CSA B64.4 specifications

Features:

Consists of two spring-loaded poppet type valves and a mechanically independent, hydraulically dependent pressure differential relief valve

Three top mounted test cocks ensure easy access during repair and maintenance when unit is installed in tight places

Note:

Create a Fire Hydrant Backflow Preventer using the RSMSA25F20T and the DMH2025F

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

ESPECIFICACIONES TÉCNICAS

| | |
|----------------------------|------------------------------|
| Material | Brass |
| Factory Part Number | BFP200 |
| Temperature Range | 33°F to 180°F (.6°C to 82°C) |
| Thread | NPT |
| Thread Size | 2" |
| Weight Lb | 40.1000 |
| Working Pressure | 175 PSIG |