

DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE PLUG MALE NPTF



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA
: 05/11/2026 09:23 AM

SKU
: 10156

MARCA
: DIXON VALVE

MODELO
: CM2M3-B

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 10,000 PSI (700 bar) Burst
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,000 PSI (400 bar) Burst

Construction:

Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:

Mold Coolant Interchange

Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	CM2M3-B
Hex	11/16"
Length	1.20"
Material	Brass
Maximum OD	0.79"
Temperature Range	-90°F to +400°F (-68°C to +205°C)

ESPECIFICACIONES TÉCNICAS

Thread	Male NPTF
Thread Size	3/8"-18
Weight Lb	0.0600