

BAYLOC® DRY DISCONNECT COUPLER X FEMALE NPT

FECHA

: 06/24/2026 09:28 AM

SKU


: 27447

MARCA

: DIXON VALVE

MODELO

: DBC67-300



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

Applications:

Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.

Use:

Use with DBA style adapters

Use with standard cam and groove dust plug sized one size larger than the dry disconnect size

Use Cam & Groove Dust Plug Size: 2-1/2"

Specifications:

Canadian registration number CRN # OH14044 all provinces

Features:

Coupler has automatic closing poppet assembly

Heavy duty construction provides long service life

Stainless steel handle allows product exposure to corrosive chemicals or washdown service

Strong handle attachment prevents bending of crank assembly

Large paddle type cam arms are standard on 3" fittings, allow for an easy grip

Construction:

Stainless steel internals

Heavy duty stainless steel handle, crank and link

Compatibility & Interchange Data:

Compatible with most other brands of cam and groove style dry disconnects

Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:

Must be used with a DBA (Dry Break Cam & Groove) Style adapter for coupler to operate. Adapter sold separately.

For pressure ratings at other temperatures, contact Dixon™.

ESPECIFICACIONES TÉCNICAS

Coupler Size	4"
Description	Cam & Groove Style
Female Thread	NPT
Female Thread Size	3"
Material	Aluminum
Maximum Operating Pressure	120 PSI at 70°F(21°C)
Factory Part Number	DBC67-300
Seal	PTFE Encapsulated FKM