

DIXON SANITARY STYLE CRIMP FERRULE



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 08/31/2026 12:01 AM

SKU

: 24072

MARCA

: DIXON VALVE

MODELO

: F32G-2766

Applications:

Recommended for food, dairy and pharmaceutical applications where increased flow capacity is important.

Construction:

Ferrules have a surface finish of 63 or better

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Holedall couplings, regardless of coupling style, are never to be used for steam service at any pressure.

Holedall fittings are not to be used with cable reinforced high-pressure hose, 4 or 6 braid wire hydraulic hose or any other service not listed in the recommendations. Consult Dixon for recommendations on usage.

For applications other than the ones list, please consult Dixon.

Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.

Media being transported through the hose should be compatible with the stem material. Compatibility of ferrule material with the environment in which it will be used is recommended. Consult the Compatibility Chart or the Dixon factory for material compatibility.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	F32G-2766
Hose ID	2"
Hose OD From	2-46/64" (2.803)
Hose OD To	2-48/64" (2.827)
Material	AISI 304 Stainless Steel
Weight Lb	0.7730