

## ABS STANDARD DRY GAUGE CENTER BACK MOUNT



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/31/2026 09:31 AM

SKU

: 14598

MARCA

: DIXON VALVE

MODELO

: GC625

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B ( $\pm$  3-2-3% accuracy)

Figure interval: 20

Minor gradient: 5

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Center back mount

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

<b>Factory Part Number</b>	GC625
<b>Mount</b>	1/8"
<b>Pressure Range</b>	0-200 PSI
<b>Size</b>	1-1/2" Face
<b>Temperature Range</b>	-40°F to 150°F (-40°C to 65.6°C)
<b>Weight Lb</b>	0.1100