

ABS STANDARD DRY GAUGE LOWER MOUNT



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/21/2026 02:35 PM

SKU

: 14684

MARCA

: DIXON VALVE

MODELO

: GL125

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B (\pm 3-2-3% accuracy)

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Lower mount

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	GL125
Figure Interval	10
Minor Gradient	2
Mount	1/4"
Pressure Range	0-100 PSI
Size	2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.1700