

## ABS STANDARD DRY GAUGE LOWER MOUNT



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/21/2026 04:05 PM

SKU

: 14701

MARCA

: DIXON VALVE

MODELO

: GL340

### Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

### Specifications:

ASME B40.1, Grade B ( $\pm$  3-2-3% accuracy)

### Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

### Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Lower mount

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

|                            |                                  |
|----------------------------|----------------------------------|
| <b>Factory Part Number</b> | GL340                            |
| <b>Figure Interval</b>     | 20                               |
| <b>Minor Gradient</b>      | 5                                |
| <b>Mount</b>               | 1/4"                             |
| <b>Pressure Range</b>      | 0-200 PSI                        |
| <b>Size</b>                | 2-1/2" Face                      |
| <b>Temperature Range</b>   | -40°F to 150°F (-40°C to 65.6°C) |
| <b>Weight Lb</b>           | 0.2300                           |