

## HAMMER UNION 1502 SERIES



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 06/24/2026 06:27 PM

SKU

: 15749

MARCA

: DIXON VALVE

MODELO

: HU1502200BW

Use:

For use in extreme high pressure applications running water, oil or mud up to 15,000 PSI NSCWP (non-shock cold working pressure)

Features:

Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal

Construction:

Red sub, blue nut

Safety notes:

Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.

Pressure rating given at ambient temperature 70°F/21°C.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

Factory Part Number	HU1502200BW
Material	Forged Steel, Schedule XXS
Maximum Operating Pressure	15000 PSI NSCWP
Size	2"
Style	Buttweld
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	23.0000