

## DIX-LOCK® N-SERIES INTERCHANGE MALE HEAD X MALE THREADED END PLUG



FECHA  
: 06/21/2026 03:22 PM

SKU  
: 25092

MARCA  
: DIXON VALVE

MODELO  
: N4M4-B

### Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 Bar)  
Maximum Working and 8,200 PSI (865 Bar) Burst  
Conforms to MIL-C-3486 and A-A-50431A standards

### Construction:

Machined components are manufactured using solid bar stock.  
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life.  
Coupling sleeve constructed of cast zinc steel

### Available Options:

316 stainless steel available in some versions upon request, contact Dixon

### Compatibility & Interchange Data:

Bowes Interchange Bayonet Style  
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock

### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

## ESPECIFICACIONES TÉCNICAS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	N4M4-B
<b>Hex</b>	1-3/16"
<b>Length</b>	3.65" (92.7mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	1.31" (33.3mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	1/2"
<b>Weight Lb</b>	0.6800