

STAINLESS PANEL BUILDER GAUGE



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 08/30/2026 06:43 PM

SKU

: 17174

MARCA

: DIXON VALVE

MODELO

: PBLSS15

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Use:

Suitable for corrosive environments

Used in gaseous and liquid media

Specifications:

ASME B40.100 Grade A $\pm 2-1-2\%$ full scale accuracy

Features:

Fits industry standard 2.56" panel hole cutout

Construction:

316L stainless steel wetted parts materials

304 stainless steel case and ring

Dial- white aluminum with black lettering; stop pin

Pointer- black aluminum

Glycerin filled

Laminated safety glass window lens

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	PBLSS15
Figure Interval	3
Material	Stainless Steel
Minor Gradient	.2
Mount	1/4" Lower Back Mount
Pressure Range	0-15 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 140°F (-20°C to 60°C)
Temperature Rating	212°F (100°C) maximum media temperature
Weight Lb	0.4785