

## AUTOMOTIVE DQC J-SERIES QUICK COUPLER SET- RETAIL PACKAGED



\* Imágenes referenciales

\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/24/2026 09:54 PM

SKU

: 17286

MARCA

: DIXON VALVE

MODELO

: PND-DQCKIT4

### Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar)

Maximum Working and 10,500 PSI (724 bar) Burst

Rated pressure for connected Brass Coupler & Steel Plug: 500 PSI (35 bar)

Maximum Working and 11,500 PSI (793 bar) Burst

Rated pressure for connected Brass Coupler & Steel Plug: 500 PSI (35 bar)

Maximum Working and 11,500 PSI (793 bar) Burst

### Construction:

Machined components are manufactured using solid bar stock.

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel sleeve and steel tubular valve

### Compatibility & Interchange Data:

Truflate Automotive Interchange

Parker 10 Series, Rectus 55KM and Tomco A2100/PT400

### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**ESPECIFICACIONES TÉCNICAS**

<b>Body Size</b>	1/4"
<b>Description</b>	(Case Qty 6 Required)
<b>Factory Part Number</b>	PND-DQCKIT4
<b>Hex</b>	Coupler - 3/4",   Plug - 9/16"
<b>Includes</b>	2JF2-B, J2M2
<b>Length</b>	Coupler - 2.04",   Plug - 1.59" (Coupler - 51.8mm,   Plug - 40.4mm)
<b>Mandatory Pkg/Box Qty</b>	6
<b>Material</b>	Coupler - Brass,   Plug - Steel
<b>Maximum OD</b>	Coupler - 0.88",   Plug - 0.65" (Coupler - 22.4mm,   Plug - 16.5mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	1/4"
<b>Weight Lb</b>	0.3600