

INDUSTRIAL DQC DF-SERIES QUICK COUPLER SET- RETAIL PACKAGED



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 04/30/2026 08:03 PM

SKU

: 17288

MARCA

: DIXON VALVE

MODELO

: PND-DQCKIT6

Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar)

Maximum Working and 8,500 PSI (586 bar) Burst

Rated pressure for connected Brass Coupler & Steel Plug: 500 PSI (35 bar)

Maximum Working and 9,000 PSI (620 bar) Burst

Rated pressure when connected with Steel F-Series Manual Couplers: 500

PSI (35 bar) Maximum Working and 6,500 PSI (448 bar) Burst

Rated pressure when connected with Brass F-Series Manual Couplers: 500

PSI (35 bar) Maximum Working and 9,000 PSI (620 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel sleeve and steel tubular valve

Compatibility & Interchange Data:

Foster 3, 4, 5 and 6 Series

Parker 30- Series Automatic Interchange & Parker 20-Series Manual Interchange

Hansen 3000, 4000, 5000 and 6000 & Hansen 1000, 400 and 500

How it works:

To disconnect, begin by holding the hose on the nipple side with three of your fingers, leaving your thumb and index finger free.

Grab the sleeve with your thumb and index finger and begin to pull the sleeve towards the palm of your hand.

After pulling the sleeve, the nipple will move out of the coupler slightly.

Continue to hold the hose and coupler sleeve until all air is fully exhausted.

After the line is fully exhausted, you are able to safely separate the nipple from the coupler.

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Description	(Case Qty 6 Required)
Factory Part Number	PND-DQCKIT6
Hex	Coupler - 3/4", Plug - 11/16"
Includes	2FM2-B, D2F2
Length	Coupler - 2.04", Plug - 1.66" (Coupler - 51.8mm, Plug - 42.2mm)
Mandatory Pkg/Box Qty	6
Material	Coupler - Brass, Plug - Steel
Maximum OD	Coupler - 0.88", Plug - 0.79" (Coupler - 22.4mm, Plug - 20.1mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	1/4"
Weight Lb	2.0500