

AG-SERIES BALL PLUG



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 07/21/2026 12:18 AM

SKU

: 27617

MARCA

: DIXON VALVE

MODELO

: RD-AG40F4

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Pioneer Agricultural Interchange

Parker/Pioneer 4000 Series, Faster NS/NV Series

Safeway Series-S20, Stucchi IR-Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Burst Pressure	16500 PSI (1100 Bar)
Hex	1-1/16"
Length	1.95" (49.5mm)
Mandatory Pkg/Box Qty	4
Material	Steel
Maximum OD	1.21" (30.7mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Factory Part Number	RD-AG40F4
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female ORB
Thread Size	3/4"-16