

STRAUB OPEN-FLEX 1L COUPLING



* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

FECHA

: 05/01/2026 01:13 AM

SKU

: 25497

MARCA

: DIXON VALVE

MODELO

: STR35201

Applications:

Suitable for repairing or joining pipes where access to the pipe end is difficult or not possible. The unique wrap-around design differs from similar type repair products because the installation or repair is permanent due to the unique flexible lip seal gasket design. Open-Flex couplings will also act as an expansion joint. Straub Open-Flex couplings do require the pipes to be properly anchored and restrained as they are not pull-out resistant like the Straub Grip-L couplings. Use Straub Open-Flex couplings to replace bolted sleeve type couplings (AWWA Stc. C-219) or for permanent repairs or installation.

Use:

Joins like or dissimilar pipe materials: steel, galvanized, painted, stainless steel, thin-wall stainless steel, PVC, copper

Use with assembly tool: STR6648

Specifications:

Built to ASTM 1476, Type C, Class 2 specifications

American Bureau of Shipping (ABS) up to 232 PSI

Underwriter's Laboratories

National Sanitation Foundation

Features:

Accommodates up to 5° of pipe misalignment

Vary gap between pipe ends

Absorbs vibration, water hammer and sound

Special patented grip ring for superior holding power on hard-surfaced pipes

5 year limited warranty

Reusable

Construction:

Highest quality 316 Ti stainless steel construction

EPDM sealing sleeve standard, temperature range of -4°F to 176°F

Casing: AISI 316 Ti

Screws: AISI 4135 steel

Bolts: AISI 12L 14 Galvanized

Installation

Requires no special tools or pipe-end preparation; only a torque wrench is required for a secure and safe pipe connection that seldom needs retightening.

Safety notes:

Not pull-out resistant.

Ensure that pipes are properly anchored and supported.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

| | |
|----------------------------|-------------------------------|
| Factory Part Number | STR35201 |
| Material | Stainless Steel |
| Pipe OD | 2.88" |
| Range | 2.81" to 2.93" |
| Size | 2-1/2" |
| Temperature Range | -4°F to 176°F (-20°C to 80°C) |
| Weight Lb | 1.8000 |
| Working Pressure | 232 PSI |