

15K THREADED NIPPLE



FECHA
: 04/17/2026 03:31 AM

SKU
: 21047

MARCA
: DIXON VALVE

MODELO
: TD4F4-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	½"
Factory Part Number	TD4F4-SS
Hex	1-5/8"
Length	2.06"
Material	316 Stainless Steel
Maximum OD	1.75"
Maximum Operating Pressure	15,000 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Thread	Female NPTF

* Imágenes referenciales

** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible

ESPECIFICACIONES TÉCNICAS

Thread Size ½" -14

Weight Lb 0.7100