

## KING CABLE® HOSE-TO-TOOL SERVICE



FECHA  
: 05/21/2026 03:20 PM

SKU  
: 25702

MARCA  
: DIXON VALVE

MODELO  
: WSR3



*\* Imágenes referenciales*

*\*\* Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

### Applications:

When hose, couplings or clamps fail, or there is an accidental separation of the assembly, King safety cables minimize damage to equipment and injuries to operators.

### Features:

King cable is the low cost answer to eliminate injuries caused by broken air hose connections

King safety cable reaches across the hose fittings to provide standby safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose.

Thoroughly tested with years of service. A positive safeguard for air hose connections- helps you meet today's safety standards.

Highly resistant to rust and corrosion

### Construction:

Wire Rope: Galvanized Carbon Steel

Ferrules: Aluminum

Springs: Galvanized Carbon Steel

### Installation

Must be installed in the extended position (no slack)

No tools needed- easy to install and remove

### Note:

Cables are shipped with safety restraint labels attached

### Safety notes:

King Safety cable must be installed in the extended position (no slack)

The Canada Occupational Safety and Health regulations Part XIII, 13:6b states: "Where an air hose is connected to a portable air powered tool used by

an employee, a restraining device shall be attached to all hose connections, in order to prevent injury to an employee in the even of an accidental disconnection of a hose."

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ESPECIFICACIONES TÉCNICAS

<b>Factory Part Number</b>	WSR3
<b>Hose ID</b>	1/2" - 2" (13mm - 50mm)
<b>Length</b>	28" (712mm)
<b>Material</b>	Galvanized Carbon Steel
<b>Maximum Operating Pressure</b>	200 PSI
<b>Size</b>	3/16" cable (5mm cable)
<b>Weight Lb</b>	0.4100